



eKoTac® Modular Adhesive

Product Identification

Product Class: Aqueous Polymer
 Product Name: Non-PVC Modular Carpet Tile Adhesive
 Trade Name: eKoTac®
 Hazardous Ingredients: None known
 *All components of this product appear on the Inventory of Chemical Substances published by the U.S. Environmental Protection Agency (EPA) under the authority of the Toxic Substances Control Act (TSCA).

Physical Data

Boiling Point: 212° F
 Vapor Density: Same as water.
 Evaporation Rate: Same as water.
 Appearance: Creamy white
 Odor: Low odor
 Weight per Gallon: 8.2 lbs.
 pH: 9.5 typical
 Percent Volatile by Weight: 34-36% (as water)
 Solubility in Water: Dispersible
 V.O.C. (grams per liter): "zero" grams/liter

Fire and Explosion Hazard Data

Flammable Limits: Non-flammable
 Flash Point: > 212 deg. F
 Flammability Classification: OSHA: None, DOT: None
 Extinguishing Media: CO2, chemical foam, water fog

Special Fire Fighting Features

Wear self-contained breathing gear when in confined area.

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

Health Hazard Data

Threshold Limit Value: Not established
 Effects of Overexposure: No known chronic overexposure effects.
 Emergency and First Aid Procedure: Eye contact may cause irritation. In case of eye contact, flush with water for 10-15 minutes. If irritation persists, consult a physician.
 Skin Contact: prolonged contact may cause slight irritation of the skin. Wash with soap and water. If swallowed, consult a physician.
 Inhalation: if symptomatic, move to fresh air. Get medical attention if symptoms occur.

Reactivity Data

Conditions to avoid: Excessive heat or cold
 Stability: Stable
 Incompatibility: None known.
 Hazardous Decomposition Products: None known;
 Normal (CO2, CO)
 Hazardous Polymerization: Will not occur

Precautions for Handling & Use

Ventilation: Local ventilation
 Protective Gloves: Recommended
 Eye Protection: Safety glasses
 Hygienic Practices: Wash with soap and water after exposure
 Respiratory Protection: Not required with adequate ventilation
 Other Protective Equipment: None
 Spills: Cover small spills with inert absorbent, then sweep up and place in waste disposal container. Dispose of in accordance with Federal, State and Local regulations.

Special Precautions/Other Comments

Precautions to be taken in handling and storing: Store inside at a temperature of 60°-100° F. Do not allow product to freeze.
 Other precautions: None

Transportation Data

D.O.T. Hazard Class: Unregulated

24-Hour Emergency

Chemtrec: 800 424 9300